## Kemet

## **Kemet Lubricating Fluids**

- Assists Kemet Diamond Products to cut and polish more effectively by absorbing frictional heat and diluting the lapping residue.
- Lubricant performance remains stable even when under high pressure.
- Manufactured from high purity chemicals.



LUBRICATING FLUIDS						
Туре	Colour	Soluble in	450ml Trigger Spray	2.5 litres	25 litres	
			Code	Code	Code	
W	Clear	Water	301201	301101	-	
W2	Yellow	Water	301202	301102	301205	
OS	Blue	Oil	301203	301103	301112	
LS	Blue	Oil/Water	301204	301104	-	
K	Clear	Oil	-	301124	301125	

LUBRICATING FLUIDS				
W	Water	A low viscosity water based fluid developed for use with types KD and W Kemet Diamond Compound.  Recommended for use on all Kemet Polishing Cloths as it helps to extend their life.		
W2	Water	A low viscosity water based fluid developed for use with Kemet Diamond Suspension, particularly when being used on Kemet Plates.		
OS	Oil	A low viscosity oil based lubricant primarily for use with Kemet Diamond Compounds such as types KD and L.  Recommended when polishing tooling, moulds and similar components.		
LS	Oil/Water	An alternative to OS Fluid soluble in oil and emulsifiable in water.  For use with Kemet Diamond Compounds and Liquid Diamond, particularly where components need to undergo a water based cleaning operation after lapping.		
К	Oil	For use with Kemet Liquid Diamond on Kemet Flat Lapping Systems. Assists smooth running of the lapping operation and helps to ensure a cleaner process.		

For particular advice on which Kemet product to use for your application, please contact our Technical Support Department at Maidstone, or your local Kemet Technical Representative.



## **KEMET INTERNATIONAL LTD**

Cuxton Road, Parkwood Trading Estate, Maidstone, Kent ME15 9NJ, United Kingdom Telephone: +44 (0)1622 755287 Fax: +44 (0)1622 670915 E-mail: sales@kemet.co.uk Website: www.kemet.co.uk

Kemet Diamond Products are manufactured under a Quality System registered by BSI. Cert No Q05919. **BS EN ISO 9002: 1994**